

1. PRODUCT INFORMATION

➤ **Product Detail:**

Trade Name: **GIBSON GOLD SEMI SYNTHETIC ENGINE SAE10W40 API SM/CF**

➤ **Manufacturer / Supplier:**

➤ **GIBSON OIL SDN. BHD.**

No. 15, Jalan Bukit 24, Bandar Seri Alam, 81750 Masai, Johor.

2. APPLICATIONS

Naturally can be used for modern gasoline engine and diesel engine s in passenger cars and light truck. Low emission passenger car and light duty vehicle engines fitted with latest catalytic converter (gasoline) or diesel particulate filter technology. Four-stroke gasoline engines in portable power equipment where the manufacturer recommends conventional passenger car motor oils.

3. TYPICAL CHARACTERISTICS

➤ **Product Typical:**

No.	Test Item	Test Methods	Test Result	Unit
1	Viscosity, Kinematic, @40°C	ASTM D445	100.8	mm ² /s
2	Viscosity, Kinematic, @100°C	ASTM D445	14.8	mm ² /s
3	Viscosity Index	ASTM D2270	152	-
4	Total Base Number, KOH	SH/T 0251	6.5	mg/g
5	Flash Point	ASTM D92	225	°C
6	Pour Point	ASTM D55950	-35	°C
7	Density, @15°C	ASTM D4052	0.858	kg/L

*The above data represents the typical laboratory value of the product, and the specific parameters are subject to the actual test.